

PAGING LOUDSPEAKER

SPT-5A, SP5-8A

DESCRIPTION

The Bogen Models SPT-5A and SP5-8A are compact, high intelligibility, reflex horn-type loudspeakers, designed for one- or two-way sound and communication systems. Their sturdy, weatherproof, all metal housing permits indoor and outdoor installation.

The Model SPT-5A has a built-in, variable-tap impedance selector switch for matching the speaker power requirements to a 25V or 70V constant-voltage line; Model SP5-8A has an 8-ohm impedance.

INSTALLATION

SETTING THE VARIABLE TAP SELECTOR SWITCH (SPT-5A)

A slotted shaft, located on the tip assembly, is used to operate a five-position selector switch. The wattage provided at each selector position is shown on the decal affixed to the rear of the speaker and in Table I.

TABLE I SPT-5A SELECTOR SWITCH SETTINGS

Position	Watts (25V)	Watts (70V)
1		.65
2	_	1.25
3	.31	2.50
4	.68	5.0
5	1.0	7.5

MOUNTING

The detachable mounting base can be used as a template to mark the mounting surface; the base has curved slots and the horn can be pivoted to adjust for optimum projection.

WIRING

A 12-inch, two-conductor cable, ribbed for phasing, is provided with each unit.

